

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 April 2004 (29.04.2004)

PCT

(10) International Publication Number
WO 2004/036217 A1

(51) International Patent Classification⁷: **G01N 33/543**,
H01L 51/20

(21) International Application Number:
PCT/EP2003/011221

(22) International Filing Date: 10 October 2003 (10.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
102 47 679.9 12 October 2002 (12.10.2002) DE

(71) Applicant (for all designated States except US): **FUJITSU LIMITED** [JP/JP]; 1-1, Kamikodanaka 4-chome, Naka-hara-ku, Kawasaki-shi, Kanagawa 211-8588 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **TORNOW, Marc**,

Uwe [DE/DE]; Tum, Walter Schottky Institut, Am Coulombwall, 85748 Garching (DE). **ABSTREITER, Gerhard** [DE/DE]; Tum, Walter Schottky Institut, Am Coulombwall, 85748 Garching (DE). **FUJITA, Shozo** [JP/JP]; Fujitsu Laboratories Limited, Atsugi 243-0197 (JP).

(74) Agents: **REICHEL, Wolfgang** et al.; Reichel und Reichel, Parkstrasse 13, 60322 Frankfurt am Main (DE).

(81) Designated States (*national*): GB, JP, US.

Declaration under Rule 4.17:

— *as to the identity of the inventor (Rule 4.17(i)) for the following designations GB, JP*


Published:

— *with international search report*
— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*


[Continued on next page]

(54) Title: SEMICONDUCTOR BASE STRUCTURE FOR MOLECULAR ELECTRONICS AND MOLECULAR ELECTRONIC-BASED BIOSENSOR DEVICES AND A METHOD FOR PRODUCING SUCH A SEMICONDUCTOR BASE STRUCTURE

A) MOLECULAR ELECTRONICS



B) BIOMOLECULAR RECOGNITION



(57) **Abstract:** The invention concerns a structured semiconductor surface as basis for molecular electronics or molecular electronics-based bio-sensors. The starting point is a heterostructure consisting of two undoped layers of a semiconductor material that are separated by an extremely thin (a few nm) layer of a different semiconductor material. This material stack is cleaved perpendicular to the layer planes and the middle layer is selectively etched. Source- and drain contacts for conductive organic "wires" are built by evaporation with a thin metal film. The middle conductive layer can be employed as electrostatic gate. An assembly for contacting a few up to single wires can be obtained by two sequential separations and evaporations. Possible organic wires are e.g. molecules with conjugated π -electron system, DNA-oligonucleotides or carbon nanotubes. By means of a further functionalisation with receptors for biomolecular recognition (antibodies, proteins) an employment as highly sensitive biosensor for detection, analysis and quantification of special biomolecules and their mutual interaction becomes possible (e.g. DNA-protein interaction).